

CIRANOVA[®]
SINCE 1929



1L

Ciranova[®] products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare
tel +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48
www.ciranova.be ciranova@ciranova.be

TECHNICAL DATA SHEET

Maintenance oil - NEW

PRODUCT DESCRIPTION

Universal quick drying maintenance oil for the maintenance of oiled wooden surfaces. Dull or worn finishes are refreshed with the application of Ciranova maintenance oil. Applying on a regular basis can avoid expensive and time-consuming renovations.

TECHNICAL DATA

VISCOSITY	+/- 25-30 SEC (DIN 4MM)
SOLID CONTENT	+/- 29,5% BY WEIGHT
DENSITY	+/- 0,87 KG/L AT 20°C
GLOSS	MATT / SATIN
COLOR	CLEAR / WHITE

USAGE

Ciranova maintenance oil is perfectly suitable for the maintenance of parquet, stairs and furniture treated with hardwaxoil as well as for the maintenance of prefinished UV Oil flooring.

PREPARATION

Prior to application, surface must be cleaned with Ciranova intensive cleaner (removal of soap rests), rinsed with water, dry and free of dust.

USER TIPS

For parquet it is recommended to apply a thin layer of Maintenance Oil, leave to impregnate for a few minutes and buff in with a white pad till hand dry. For smaller surfaces product can be applied with a lint-free cloth. Excess must be removed.

DRYING TIMES



For normal climatic conditions a drying time of approx. 4 hr. is realistic, we advise not to charge the treated surface the first 12 hours. Deviating climatic conditions, such as lower temperature or higher humidity, can extend the drying time significantly.

APPLYING QUANTITY



+/- 40-60 m²/l. Surface condition and character of the finish have a strong influence on the consumed quantity. For optimal result, be sure to remove the excess.

MAINTENANCE

To keep the floor in perfect condition, we recommend that you follow the maintenance program of Ciranova.

Clean regularly with flooringsoap Ciranova. Depending on the use of the floor, use maintenance oil 1 time a year. For thorough cleaning, use Intensive Cleaner Ciranova[®].

PRODUCT INFORMATION

Shelf life: up to 2 years in un-opened and original packaging.

SPECIAL QUALITIES

Used cloths or pads should be plunged in water because of the danger of spontaneous combustion.