

Maintenance oil



5L 1L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-Roeselare

Belgium

tel. +32 (0) 51 30 11 40

fax +32 (0) 51 31 26 48

ciranova@ciranova.be

PRODUCT DESCRIPTION

Universal maintenance system for oiled wooden floors. For the maintenance of floors treated with flooring oil and UV-oil. Different colours available.

TECHNICAL DATA

FYSISCHE TOESTAND	fluid
APPEARANCE	dark yellow
SOLID CONTENT	26%

USE

To maintain floors treated with Hardwaxoil and UV-oil.

PREPARATION

With Hardwaxoil treated wood: remove soap rests with pure water and let dry. If strongly dirty, clean first with Intensive Cleaner Ciranova®.

USER TIPS

Apply a thin layer of Maintenance Oil Ciranova® and let impregnate for a few minutes. Wipe off with a clean cloth. Polish the oil well dry to avoid sticking.



DRYING TIMES

Do not charge the first 12 hours!

The optimal hardness is reached after 48 hours. Don't use any water or maintenance products during this period.



APPLYING QUANTITY

50 m²/l for the maintenance of already treated wooden floors.

AFTER TREATMENT

It's recommended to treat the floor each year with Maintenance Oil Ciranova®.

SPECIAL QUALITIES

Used cloths need to be thrown into water after use, to increase flammability. The presence of linseed oil in the system causes this measure. Oil Refresh Ciranova® protects your parquet floor against water and your wood gets a natural view.