

UNICARE X-MATT



0,75L

PRODUCT DESCRIPTION

UNICARE X-MATT is a universal maintenance product, which provides an extra layer of protection for all types of MATT varnished floors. UNICARE X-MATT can also be used on laminate, LVT and on our matt, water-based finishes (Ecofix & OCULTO). UNICARE X-MATT provides an extra protective film and removes micro-scratches, so that the original look of the floor is maintained. The extra matt protection ensures that the coating lasts longer and prevents adhesion of dirt.

TECHNICAL DETAILS

APPEARANCE	COLOURLESS
VISCOSITY	THIN LIQUID
DENSITY	1,05
PH VALUE	8
LUSTRE	MATT

PRE-TREATMENT

Before using UNICARE X-MATT, the varnish layer must have hardened for at least 10 days. Ensure that the floor is clean before applying the Hard Floor polish. You can clean the floor with Hard Floor Fresh. Apply the UNICARE X-MATT to a dry and grease-free surface.

INSTRUCTIONS FOR USE

Use the UNICARE X-MATT undiluted. Apply UNICARE X-MATT evenly with a microfiber cloth or a mop, in the direction of the wood grain. If necessary, a second coat of UNICARE X-MATT may be applied after 1 hour.



DRYING TIME

Approx. 1 hour at room temperature.



COVERAGE

+/- 60-80m²/ litre.

AFTER-TREATMENT

For the regular maintenance of varnished floors and floors treated with UNICARE X-MATT, use Ciranova Hard Floor fresh. To remove old coats of UNICARE X-MATT, use Ciranova Hard Floor Cleaner.

PRODUCT INFORMATION

- Shelf life : 18 months in original and unopened container.
- Store under frost-free conditions.

SPECIAL INDICATIONS

After use, clean tools with water.

Do not mix with other cleaning products. Keep out of reach of children.

Ciranova[®] products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee cannot be derived out the text of this technical description.

PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare tel +32
(0) 51 30 11 40 fax +32 (0) 51 31 26 48
www.ciranova.be ciranova@ciranova.be